

RSCWN | RKCWN



Be Certain with Belden

M12 Field Attachable Connectors (Stainless Steel Hardware)

RSCWN | RKCWN

Technical Data

Environmental

Degree of protection IP 67 / NEMA 6P
Operating temperature range -25°C (-13°F) / +85°C (+185°F)

Mechanical

Housing / Molded body PBT
Insert PBT
Contact CuZn, pre-coppered, CuSnZn
8-poles pre-nickel, gold-plated
Receptacle shell stainless steel
O-ring FKM
Mode of connection Screw terminals
Connectable conductor 4-5 poles max. 0.75 mm²
8 poles max. 0.50 mm²

Electrical

Contact resistance ≤ 5 mΩ
Nominal current at 40°C 4-5 poles 4 A
8 poles 2 A
Nominal voltage 4 poles 240 V
5 poles 60 V
8 poles 30 V
Rated voltage 4 poles 250 V
5 poles 63 V
8 poles 36 V
Test voltage 4 poles 2.0 kV eff. / 60 s
5 poles 1.5 kV eff. / 60 s
8 poles 0.9 kV eff. / 60 s
Insulation resistance > 109 Ω
Pollution degree 3

Part Number		Pins	Cable Diameter Range	Characteristics
Male	Female			
RSCWN 4/7	RKCWN 4/7	4	Ø 3.0-6.5 mm /SW 15	
RSCWN 4/9	RKCWN 4/9		Ø 4.0-8.0 mm /SW 19	
RSCWN 5/7	RKCWN 5/7	5	Ø 3.0-6.5 mm /SW 15	
RSCWN 5/9	RKCWN 5/9		Ø 4.0-8.0 mm /SW 19	

Field Attachable
Connectors