



Inductive Proximity Switch

Series M30

Description **KIN-M30PÖ/015-KL2I**

Article number **6532708002**

Wiring Diagram



Identifying characteristics in accordance with EN 60947-5-2

Electrical data		
Sensor operation (delivery status)		
Rated operating distance	S_n	15 mm
Standard target		45 mm x 45 mm, t = 1 mm, material: FE360
Real sensing distance	S_r	13,5 ... 16,5 mm
Assured operating distance	S_a	0 ... 12,2 mm
Switching element function		DC, N.C.
Repeat accuracy	R	≤ 5 %
Differential travel (hysteresis)	H	≈ 8 %
Rated operational voltage	U_e	12 - 24 V DC
Operational voltage range	U_B	10 - 30 V DC
Rated insulation voltage	U_i	75 V DC
Rated impulse withstand voltage	U_{imp}	500 V
Voltage drop	U_d	≤ 2 V specification
Utilization category		DC 13
Rated operational current	I_e	200 mA ±10 %
Minimum operating current	I_m	1 mA
Off-state current	I_r	< 0,1 mA
No-load supply current	I_o	< 10 mA
Switching element		permanent overload and s.c.p.
Short-circuit protection		pulsed, current-limited and thermal
Frequency of operating cycles	f	100 Hz
Mounting		non flush
False polarity protection		yes
Time delay before availability	t_v	< 300 ms
IO-Link operation		 IO-Link
Rated operating voltage range	U_B	18 - 30 V DC (typ. 24 V DC)
Output		IO-Link
Switching element function		N.O. / N.C. parameterizable
Repeat accuracy	R	≤ 5 % from the end value, U_B and temperature at a constant level
No-load supply current	I_o	< 15 mA
Serial output		Short-circuit proof
False polarity protection		yes

IO-Link specification

IO-Link Spec V 1.1	compliant (yellow LED)	
Speed	COM 2	38,4 kBaud
Process data Device→Master	8 bit	
cycle time	10 ms	

Mechanical Data

Front cap	LCP, black	
Enclosure	brass, nickel plated	
End cap	PA12, transparent	
Ambient air temperature	-25 °C ... +70 °C	
Type of protection	IP67 / NEMA Type 1	
Function indication	LED, yellow	
Degree of pollution	3 (Pollution of the sensing surface may decrease operating distance)	
Termination type	Cable 3 x 0,34 mm ² x 2 m, PUR - Outer jacket, black	
For attachment	2 x hexagon nut (tightening torque ≤ 70 Nm)	

Product reliability (in acc. with DIN EN 61709 (SN 29500))

MTTF (at 40 °C)	>1150 years
-----------------	-------------

EU Conformity

acc. to directive 2014/30/EU (EMC-Directive)
--

Approvals



Notes

To be used with a class 2 power supply according to UL approval.

Further data and information can be found at www.bernstein.eu.