ST 7PNG

III, di-soric

- Teach output for remote teach
- Automatic detection pnp/npn/push-pull
- 视觉和听觉信号
- Buzzer can be switched off
- Operation via batteries and external power supply
- 快速安装用卡槽
- Automatic switch-off
- 紧凑的设计重量轻
- Shock protection trough silicone casing





Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments. These instruments shall exclusively be used by qualified personnel.



TECHNICAL INFORMATION (typ.)	+20°C, 24V DC
尺寸	141 x 82 x 34 mm (尺寸)
内部功耗	< 40 mA
输出电压	18 V DC
防护等级	IP 21
用于	pnp, npn and push-pull sensors
连接	quick-action sockets
电流限制值	60 mA in battery operation, 240 mA in operation with external power supply
交货范围	3个1.5V AA碱性电池

di-soric GmbH & Co. KG ■ Steinbeisstraße 6 ■ DE-73660 Urbach

209540

Fon + 49 (0) 71 81 / 98 79 - 0
Fax + 49 (0) 71 81 / 98 79 - 179
info@di-soric.com www.di-soric.com © di-soric | Subject to modifications | 23/02/20 | Page 1 (1)