## ZR 06B-TSSL Counting Module with Reset Function



- 6 lines LCD display
- Quick and simple mounting directly on the sensor
- Pluggable without any wiring (work)
- Long-term storage of values thanks to back-up battery
- Reset via key
- Robust metal casing




BK = black BN = brown BU = blue	+ <u>BN 1</u> S <u>BK 4</u> - <u>BU 3</u>	ZRx 06B-xxx	BK 4 S H ZRR 06B-IBS
BU = blue WH = white	- 0 - 50 - 5		BU 3

## Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.

These instruments shall exclusively be used by qualified personnel.



TECHNICAL INFORMATION (typ.)	+20°C, 24V DC
Service voltage	10 35 V DC
No-load current	3 mA
Display	6 lines LCD display, LED yellow (Display output)
Countering frequency	10000 Hz
Reset of counter	Reset key
Ambient temperature, operation	-10 +60 °C
Insulation voltage endurance	500 V
Protection class	IP 67
Casing material	Aluminium black anodized
Connection	Connector, M8, 3-poled
Connection 2	Cable 100 mm, Connector, M8, 3-poled

di-soric GmbH & Co. KG ■ Steinbeisstraße 6 ■ DE-73660 Urbach

203212

Fon + 49 (0) 71 81 / 98 79 - 0 
Fax + 49 (0) 71 81 / 98 79 - 179 
info@di-soric.com www.di-soric.com © di-soric | Subject to modifications | 20/02/20 | Page 1 (1)