ZRR 06B-IBS Counting Module with Reset Function



- 6 lines LCD display
- Quick and simple mounting directly on the sensor
- Pluggable without any wiring (work)
- Long-term storage of values thanks to back-up battery
- Reset via key or connection
- Robust metal casing





Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.

These instruments shall exclusively be used by qualified personnel.



TECHNICAL INFORMATION (typ.)	+20°C, 24V DC
Service voltage	10 35 V DC
No-load current	3 mA
Display	6 lines LCD display, LED yellow (Display output)
Countering frequency	10000 Hz
Reset of counter	Reset key, Remote reset
Ambient temperature, operation	-10 +60 °C
Insulation voltage endurance	500 V
Protection class	IP 67
Casing material	Aluminium black anodized
Connection	Connector, M12, 4-poled

di-soric GmbH & Co. KG ■ Steinbeisstraße 6 ■ DE-73660 Urbach

203213

Fon + 49 (0) 71 81 / 98 79 - 0 🖩 Fax + 49 (0) 71 81 / 98 79 - 179 🖩 info@di-soric.com 🖷 www.di-soric.com 🖤 @ di-soric | Subject to modifications | 20/02/20 | Page 1 (1)