



DCC 08 VH 02 NSK/140

Inductive Proximity Switch


- High-temperature resistant up to 140 °C permanent temperature
- Stainless steel casing
- Active zone LCP
- Integrated amplifier
- Short-circuit protection
- Starting pulse suppression



Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.

These instruments shall exclusively be used by qualified personnel.



TECHNICAL INFORMATION (typ.)		+20°C, 24V DC
Operating principle		Inductive
Evaluation		digital
Size		M8 x 1 (thread)
Design		screw
Mounting		flush
Characteristics		up to 140 °C, high-temperature resistant
Operating distance		2 mm
Standardized measuring plate		8 x 8 x 1 mm
Service voltage		10 ... 30 V DC
No-load current		< 10 mA
Switching output		npn, 120 mA, NO
Switching hysteresis		3 ... 15 %
Shock/vibration load		10 ... 55 Hz / 1,0 mm / 30 g
Voltage drop		< 2,0 V
Switching frequency		600 Hz
Ambient temperature, operation		0 ... +140 °C
Insulation voltage endurance		500 V
Protection class		IP 65
Casing material		stainless steel LCP
Material		Silicone (Cable)
Connection		Cable, 2,0 m