


BE-A50/50-G5-K-BS

High power barlight




- High light intensity
- A minimal edge region
- Homogenous luminous field
- Very compact design
- High protection class IP 67
- Robust design



Safety instructions

The Instruments are not to be used for safety applications, in particular applications in which safety of persons depends on proper operation of the instruments.

These instruments shall exclusively be used by qualified personnel.



TECHNICAL INFORMATION (typ.)	+20°C, 24V DC
Design	Barlight
Illuminated area	50 x 50 mm
Light colour	White, 5000 K
Emission angle FWHM	130°
Illumination intensity	5.8 klx (0.1 m), 1.6 klx (0.2 m), 790 Lux (0.3 m)
Service voltage	24 V DC (Supply Class 2)
No-load current	118 mA, (24 V DC)
Power	2,8 W (24 V DC)
Shock-/vibration load	10 ... 55 Hz / 1,0 mm / 30 g
Inverse polarity protection	No
Ambient temperature, operation	0 ... +40 °C (permanent operation)
Protection class	IP 67
Protection degree	III, operation on protective low voltage
Risk group (DIN EN 62471)	Free group
Casing material	Aluminium black anodized
Material	PMMA, clear (Protection optics)
Connection	Cable, 0,3 m, with connector, M12, 3-poled
Weight	90 g
Connecting cable	VK ...