




I/O-junction passive, Ø8mm snap, Top



Product data

Item description	4/OS8-3P1T
Item-No.	8062601
Customs tariff-No.	85366990
Step-File	4I_OS8_3P1T.stp
EAN	4047106148768

Technical data

I/O-junction	4-way, with connecting plug, M12
I/O-slot	female, 8 mm snap
Number of pins	3
Rated voltage	30V
Current load (at 40°C)	4A
Total current load	4A
Insulation resistance	$\geq 10^9 \Omega$
Resistance	$\leq 5 m\Omega$
Ambient temperature product	-30°C...+90°C
Number of LEDs	1
Number of I/O-slots	4
Circuit logic	pnp
Operating voltage-indicator	LED GN
Contact material	Metal, CuZn, gold-plated
Contact-carrier material	Plastic, PA, BK
Sealing (female) material	FPM/FKM
Housing material	Plastic, PA, BK
Connecting type	Top

Thread insert material	Metal, CuZn
Standards	IEC 61076-2-104
Degree of protection (mounted)	IP65, IP67
Mechanical life-cycle	>100 mating cycles
Connecting plug	M12x1, 8 poles
Sealing material, connecting-plug	Plastic, FPM/FKM
Receptacle housing material, connecting-plug	Metal, CuZn, nickel-plated
Contact material, connecting-plug	Metal, CuZn, gold-plated
Contact-carrier material, connecting-plug	Plastic, PA, BK
Mechanical life-cycle, connecting-plug	>100 mating cycles
Number of pins, connecting-plug	8
Degree of protection, connecting-plug (mounted)	IP65, IP67
Degree of pollution	3

Allocation chart

I/O	1	2	3	4	all (+)	all (-)
Pin	4	4	4	4	1	3
M12	1	2	3	4	5	7
Cable Accessories	WH	BN	GN	YE	GY	BU

Classification

eCl@ss 6.0	27279219
eCl@ss 7.0	27279219
eCl@ss 8.0	27279219
eCl@ss 9.0	27440108
ETIM 5.0	EC002585
ETIM 6.0	EC002585

Accessories

Single-ended cordset, Automation Line, M12

<https://www.escha.net/en/Products/Standard/SensorActuator-connectors/8046904/M12-female-straight-sensor/actuator-cable-8-poles-A-coded>

Single-ended cordset, Automation Line, M12

<https://www.escha.net/en/Products/Standard/SensorActuator-connectors/8046907/M12-female-angled-sensor/actuator-cable-8-poles-A-coded>