



Single-ended cordset, M23



Product data	
Item description	MKCU19.003-10/S370
Item-No.	8017222
Length	10m
Customs tariff-No.	85444290
Step-File	MKCU19.stp
EAN	4047106065423
Technical data	
Connector	female, straight, M23
Number of pins	19
Pin assignment	1 VT, 2 RD, 3 GY, 4 RDBU, 5 GN, 6 BU, 7 GYPK, 8 WHGN, 9 WHYE, 10 WHGY, 11 BK, 12 GNYE, 13 YE BN, 14 BNGN, 15 WH, 16 YE, 17 PK, 18 GYBN, 19 BN
Rated voltage	125V
Current load power	10A contacts 6,12,19
Current load signal	4A, all other contacts
Insulation resistance	$\geq 10^9 \Omega$
Ambient temperature product	-30°C...+90°C
Contact material	Metal, CuZn, gold-plated
Contact-carrier material	Plastic, PBT, WH
Grip body material	Plastic, TPU, BU
Coupling nut material	Metal, CuZn, nickel-plated
Sealing (female) material	Plastic, NBR
Degree of protection (mounted)	IP65, IP67
Mechanical life-cycle	>100 mating cycles
Cable end assembly	open cable end
Degree of pollution	3

Cable		PUR, UL, S370
Flexible, silicone- and halogen-free control line with high mechanical strength. The cable is chemicals, hydrolysis-, and microbes- resistant. The drag-chain application is possible at a bending radius of minimum 10 x d. Due to its weld-field immunity, the cable is very well suited for the flexible application in robotics, machine-tool, and metal-cutting production. The cables meet the UL and CSA (UL10493/20549; cULus) requirements.		
Outer diameter of jacket	9,7 mm	
Cable-jacket material	PUR	
Jacket color	BK, similar RAL9005	
Wire cross-section	16 x 0.34 mm ² + 3 x 1 mm ²	
Wire insulation material	PP	
Wire colors	VT, RD, GY, GN, BK, WH, PK, YE, RDBU, GYPK, WHGN, WHYE, WHGY, YEBN, BNGN, GYBN, BN, BU, GNYE	
Bending radius (repeated)	min. 10 x Ø-cable	
Temperature range (repeated)	-5°C...+80°C	
Temperature range (fixed)	-40°C...+80°C	
Drag chain-application	2 Mio. cycles	
Halogen-free	Yes	
Special features	flame retardant, LABS free, RoHs compliant, drag chain-adapted, halogen free	
Classification		
eCl@ss 6.0	27279218	
eCl@ss 7.0	27279218	
eCl@ss 8.0	27279218	
eCl@ss 9.0	27060311	
ETIM 5.0	EC001855	
ETIM 6.0	EC001855	