

## Double-ended cordset, 10 GBit/s, Industrial Ethernet, RJ45



Product data		
Item description	IE-RJ45SS8.002-10-IE-RJ45SS8.012/S620GY	
Item-No.	8077562	
Length	10m	
Customs tariff-No.	85444290	
Step-File	IE-RJ45SS8-m-IE-RJ45SS8_S620.stp	
EAN	4047106179434	
Label-carrier	2 pieces	
Technical data	A-side	B-side
Connector	male, straight, RJ45	male, straight, RJ45
Number of pins	8	8
Pin assignment	1 WH/OG, 2 OG; 3 WH/GN, 4 BU; 5 WH/BU, 6 GN; 7 WH/BN, 8 BN	1 WH/GN, 2 GN; 3 WH/OG, 4 WH/BN; 5 BN, 6 OG; 7 BU, 8 WH/BU
Allocation	Crossover	Crossover
Rated voltage	50V	50V
Current load (at 40°C)	1A	1A
Insulation resistance	≥10 <sup>9</sup> Ω	≥10 <sup>9</sup> Ω
Transmission features	Cat6A	Cat6A
Ambient temperature product	-40°C...+70°C	-40°C...+70°C
Contact material	Metal, CuZn, gold-plated	Metal, CuZn, gold-plated
Contact-carrier material	Plastic	Plastic
Grip body material	Plastic, TPE, BK	Plastic, TPE, BK
Shielding	with shielding	with shielding
Material of shielding housing	Metal, CuZn, nickel-plated	Metal, CuZn, nickel-plated
Standards	IEC 60603-7-5	IEC 60603-7-5
Degree of protection (mounted)	IP20	IP20
Mechanical life-cycle	>1000 mating cycles	>1000 mating cycles
Degree of pollution	1	1

cable		Cat7, FRNC, UL, S620
<p>High-grade, shielded S/FTP PiMF-data cable, specified up to 600 MHz, with halogen-free outer jacket. The cable complies with the transmission requirements of category 7 according to EN 50288-4-2 and IEC 61156-5. Due to the lean structure and the possible bending radiuses, the flexible AWG27/7-cabele is best adapted for applications in structured wiring according to ISO/IEC 11801 and EN 50173 in buildings, and server cabinets. Ideal solutions for all applications of class EA according to IEEE802.3an, VoIP, and PoE. The cable outperforms the preconditions for the compliance with electromagnetic interference class B according to EN 55022 as well as electromagnetic immunity according to EN 55024. The cable is available in grey, yellow, blue, red, green, and black. The cables meet the UL 444 Communication Cable CMG requirements.</p>		
Outer diameter of jacket	6,00 mm	
Cable-jacket material	flame retardant, halogen free compound	
Jacket color	GY, similar RAL7035	
Wire cross-section	4 x 2 x AWG27	
Wire insulation material	PE	
Wire colors	WH/BU,BU ; WH/OG,OG ; WH/GN,GN ; WH/BN,BN	
Conductor structure	7 x 0,14 mm	
Bending radius (fixed)	5 x Ø-cable	
Temperature range (fixed)	-20°C...+60°C	
Shielding	Yes	
Halogen-free	Yes	
Transmission features	Cat7	
Cable test voltage	1kV	
Rated voltage cable	125V	
Special features	flame retardant, RoHs compliant, halogen free, low emission of smoke, high flexibility, no corrosive gases	
Classification		
eCl@ss 7.0	27060308	
eCl@ss 8.0	27060308	
eCl@ss 9.0	27060308	
ETIM 5.0	EC002599	
ETIM 6.0	EC002599	
Accessories		Web-Link
Unlocking clip for RJ45	<a href="https://www.escha.net/en/products/accessoires/unlocking-clips-for-rj45/">https://www.escha.net/en/products/accessoires/unlocking-clips-for-rj45/</a>	