



## Y-splitter, M12, M8 - M8, with cable outlet



### Product data

Item description	YK-FS4M12-2AL-SWKP4P2-0,6/0,6/P00
Item-No.	8076050
Length	0.6m
Customs tariff-No.	85444290
Step-File	YK-FS4M12-2AL-SWKP4P2-L_L.stp
EAN	4047106174088

	Exit 0	Exit 1	Exit 2
Connector	male, M12, straight	female, M8, angled, with LED	female, M8, female, with LED
Contact-carrier material	Plastic, TPU, BK	Plastic, TPU, BK	Plastic, TPU, BK
Coupling nut material	Metal, CuZn, nickel-plated	Metal, CuZn, nickel-plated	Metal, CuZn, nickel-plated
Grip body material	Plastic, TPU, BK	Plastic, TPU, transparent	Plastic, TPU, transparent
Rated voltage	60V	30V	30V
Coding of	A	A	A
Number of pins	4	4	4
Current load (at 40°C)	4A	3A	3A

Insulation resistance  $\geq 10^9 \Omega$

Ambient temperature product  $-30^\circ\text{C} \dots +90^\circ\text{C}$

Operating voltage-indicator LED GN

Signal status-indicator LED YE

Circuit logic pnp

Sealing (female) material FPM/FKM

Mechanical life-cycle  $> 100$  mating cycles

Standards IEC 61076-2-101

Degree of protection (mounted) IP65, IP67, IP68

Degree of pollution 3

Cable	PVC, P00, GY
PVC-cable for measurement and control-, and sensor technology. Suitable for applications in dry areas on packaging machines, assembly- and conveyor technology. High flexibility with unstressed movement (conditional drag-chain application possible). Predestined for applications in food- and beverage industry.	
Outer diameter of jacket	4,20 mm
Cable-jacket material	PVC
Jacket color	GY, similar RAL7040
Wire cross-section	4 x 0.25 mm <sup>2</sup>
Wire insulation material	PVC
Wire colors	BN, WH, BU, BK
Conductor structure	14 x 0.15 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Temperature range (repeated)	0°C...+80°C
Temperature range (fixed)	-25°C...+80°C
Rated voltage cable	≤300 V
Special features	seawater resistant, recyclable, LABS free, RoHs compliant, acid- and alkali resistant, ozone resistant, UV resistant
Classification	
eCl@ss 6.0	27279218
eCl@ss 7.0	27279218
eCl@ss 8.0	27279218
eCl@ss 9.0	27060313
ETIM 5.0	EC001855
ETIM 6.0	EC001855