



## Double-ended cordset, Automation Line, M12



### Product data

|                    |                       |
|--------------------|-----------------------|
| Item description   | AL-WAK3-5-AL-WAS3/P00 |
| Item-No.           | 8051461               |
| Length             | 5m                    |
| Customs tariff-No. | 85444290              |
| Step-File          | AL-WAK3_AL-WAS3.stp   |
| EAN                | 4047106021474         |
| Label-carrier      | 2 pieces              |

| Technical data                 | A-side                     | B-side                     |
|--------------------------------|----------------------------|----------------------------|
| Connector                      | female, straight, M12      | male, straight, M12        |
| Number of pins                 | 3                          | 3                          |
| Pin assignment                 | 1 BN, 3 BU, 4 BK           | 1 BN, 3 BU, 4 BK           |
| Coding of                      | A                          | A                          |
| Rated voltage                  | 250V                       | 250V                       |
| Current load (at 40°C)         | 4A                         | 4A                         |
| Insulation resistance          | $\geq 10^9 \Omega$         | $\geq 10^9 \Omega$         |
| Resistance                     | $\leq 5 m\Omega$           | $\leq 5 m\Omega$           |
| Ambient temperature product    | -30°C...+90°C              | -30°C...+90°C              |
| Contact material               | Metal, CuSn, gold-plated   | Metal, CuSn, gold-plated   |
| Contact-carrier material       | Plastic, TPU, BK           | Plastic, TPU, BK           |
| Grip body material             | Plastic, TPU, BK           | Plastic, TPU, BK           |
| Coupling nut material          | Metal, CuZn, nickel-plated | Metal, CuZn, nickel-plated |
| Sealing (female) material      | FPM/FKM                    |                            |
| Standards                      | IEC 61076-2-101            | IEC 61076-2-101            |
| Degree of protection (mounted) | IP65, IP67, IP68           | IP65, IP67, IP68           |
| Mechanical life-cycle          | >100 mating cycles         | >100 mating cycles         |
| Degree of pollution            | 3                          | 3                          |

| <b>Cable</b>  |  |
|---|--|
|   | <b>PVC, P00, GY</b>  |
| PVC-cable for measurement and control-, and sensor technology. Suitable for applications in dry areas on packaging machines, assembly- and conveyor technology. High flexibility with unstressed movement (conditional drag-chain application possible). Predestined for applications in food- and beverage industry. |  |
| Outer diameter of jacket  | 4,20 mm  |
| Cable-jacket material   | PVC  |
| Jacket color  | GY, similar RAL7040  |
| Wire cross-section  | 3 x 0.34 mm <sup>2</sup>   |
| Wire insulation material  | PVC  |
| Wire colors   | BN, BU, BK   |
| Conductor structure   | 19 x 0.15 mm   |
| Bending radius (fixed)  | 5 x Ø-cable  |
| Bending radius (repeated)   | 10 x Ø-cable   |
| Temperature range (repeated)  | 0°C...+80°C  |
| Temperature range (fixed)   | -25°C...+80°C  |
| Rated voltage cable   | ≤300 V   |
| Special features  | seawater resistant, recyclable, LABS free, RoHs compliant, acid- and alkali resistant, ozone resistant, UV resistant |
| <b>Classification</b>   |  |
| eCl@ss 6.0  | 27279218   |
| eCl@ss 7.0  | 27279218   |
| eCl@ss 8.0  | 27279218   |
| eCl@ss 9.0  | 27060311   |
| ETIM 5.0  | EC001855   |
| ETIM 6.0  | EC001855   |
| <b>Accessories</b>  |  |
| <b>Mounting-set, M12</b><br><a href="https://www.escha.net/en/Products/Standard/Accessories-for-connectivity/8047664/Mounting-set-M12-clips-and-screws-M4x8-black">https://www.escha.net/en/Products/Standard/Accessories-for-connectivity/8047664/Mounting-set-M12-clips-and-screws-M4x8-black</a>                   |  |
| <b>Torque-wrench set</b><br><a href="https://www.escha.net/en/Products/Standard/Accessories-for-connectivity/8055431/Torque-wrench-set-M8-M12">https://www.escha.net/en/Products/Standard/Accessories-for-connectivity/8055431/Torque-wrench-set-M8-M12</a>   |  |
| <b>Marking rings Ø 9mm</b><br><a href="https://www.escha.net/en/products/standard/accessories-for-connectivity/?p=1&amp;o=3&amp;n=15&amp;f=809">https://www.escha.net/en/products/standard/accessories-for-connectivity/?p=1&amp;o=3&amp;n=15&amp;f=809</a>   |  |