


## Single-ended cordset, High temperature, M8x1









Product data	
Item description	HT-SWKP4-10/S2430
Item-No.	8037216
Length	10m
Customs tariff-No.	85444290
Step-File	HT-SWKP4_S2430.stp
EAN	4047106001018
Technical data	
Connector	female, angled, M8x1
Number of pins	4
Pin assignment	1 BN, 2 WH, 3 BU, 4 BK
Rated voltage	60V
Current load (at 40°C)	4A
Insulation resistance	≥10°Ω
Ambient temperature product	-20°C+150°C
Contact material	Metal, CuZn, gold-plated
Contact-carrier material	Plastic, PBT GF, BK
Grip body material	Plastic, PBT GF, BK
Coupling nut material	Metal, CuZn, nickel-plated
Sealing (female) material	FPM/FKM
Standards	IEC 61076-2-104
Degree of protection (mounted)	IP65
Mechanical life-cycle	>100 mating cycles
Cable end assembly	50mm stripped
Degree of pollution	3/2



## Cable PTFE, S2430, high temp

The thermal resistance of this high-temperature cable extends from -190°C to +260°C. Due to its fully fluorinated jacket and wire insulation, the cable is perfectly suited for applications in high-frequency cables, as control cable in critical temperature areas, and in the computer-, and aviation industry. In addition, it stands out through a very good chemical strength, as well as its ozone- and weather resistance.

dustry. In addition, it stands out through a very good chemical strength	, as well as its ozone- and weather resistance.
Outer diameter of jacket	3,80 mm
Cable-jacket material	PTFE
Jacket color	WH, similar RAL9003
Wire cross-section	5 x AWG22
Wire insulation material	PTFE
Wire colors	BN, WH, BU, BK, GY
Conductor structure	7 x 0.254 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Temperature range (fixed)	-190°C+260°C
Rated voltage cable	≤250 V
Special features	seawater resistant, LABS free, RoHs compliant, ozone resistant, UV resistant, hydrolysis proof, flexibility at low temperature, non-flammable, low emission of smoke, excellent chemicals resistance, flexible at high tempe-
	ratures
Classification	-
Classification eCl@ss 6.0	-
	ratures
eCl@ss 6.0	ratures 27279218
eCl@ss 6.0 eCl@ss 7.0	27279218 27279218
eCl@ss 6.0 eCl@ss 7.0 eCl@ss 8.0	ratures  27279218  27279218  27279218
eCl@ss 6.0 eCl@ss 7.0 eCl@ss 8.0 eCl@ss 9.0	27279218 27279218 27279218 27279218 27060311
eCl@ss 6.0 eCl@ss 7.0 eCl@ss 8.0 eCl@ss 9.0 ETIM 5.0	ratures  27279218  27279218  27279218  27060311  EC001855
eCl@ss 6.0 eCl@ss 7.0 eCl@ss 8.0 eCl@ss 9.0 ETIM 5.0 ETIM 6.0	27279218 27279218 27279218 27279218 27060311 EC001855 EC001855
eCl@ss 6.0 eCl@ss 7.0 eCl@ss 8.0 eCl@ss 9.0 ETIM 5.0 ETIM 6.0 Accessories	ratures  27279218  27279218  27279218  27060311  EC001855  EC001855  Web-Link
eCl@ss 6.0 eCl@ss 7.0 eCl@ss 8.0 eCl@ss 9.0 ETIM 5.0 ETIM 6.0 Accessories Mounting-set, M8x1	ratures  27279218  27279218  27279218  27060311  EC001855  EC001855  Web-Link  https://www.escha.net/en/search?sSearch=8047663
eCl@ss 6.0 eCl@ss 7.0 eCl@ss 8.0 eCl@ss 9.0 ETIM 5.0 ETIM 6.0 Accessories Mounting-set, M8x1 Torque-wrench set	27279218 27279218 27279218 27279218 27060311 EC001855 EC001855 Web-Link https://www.escha.net/en/search?sSearch=8047663 https://www.escha.net/en/search?sSearch=8055431