


[Article Page](#)

Product Description

connector M12



Name	V2-4/W/P/5m
Order number	44505123912
Matchcode	9512-3912
Connection	 Socket
Leaving	gewinkelt

Technical Specification

Special features	Flexible cable conduit capable
	Silicone-free
Signal type	connector
Operating temperature	-25 ° C to 80 ° C
Protection category	IP 68
Cable	offen
Number of terminals	4
Rated operating current at 40° C	4 A
Rated operating voltage	
Contact resistance	≤ 5 mΩ
Isolation resistance	≥ 100 MΩ
Cable length	5 m

Utilisation category	3
Contact durability	≥ 100
Contact material	CuSn
Contact surface material	Ni/Au
Contact holder	PUR
Shell type material	PUR
Knurled nut material	Messing vernickelt
Sealing material	NBR
Cable material	PUR
Cover material	Li9Y11Y
Wire isolation material	TPM
Wire material	Cu Litze
Wiring diameter	4x0,34
Signal wire structure	42x0,10mm
Conductor diameter	1,27 mm 0,02 mm
Outer cover diameter	4,7 mm $\pm$ 0,2 mm
Conductor colour	braun, weiß, blau, schwarz
Cover colour	schwarz
Wire resistance	max. 58Ω/km
Nominal operating voltage	≤ 24 V
Test voltage unit	≥ 3000
Flame-retardant	nach UL-Style 20549
Halogen-free	nach DIN VDE 0472 Teil 815
Oil-resistant	nach DIN EN 60811-2-1
Other resistances	Highly resistant to acids, alkaline solutions and solvents, hydrolisis and microbe resistant
Notes	Kodierung: A-Standard Anzugsdrehmoment: 0,8 - 1,2 Nm

Errors and omissions exceptet