


[Article Page](#)

Product Description	inductive sensor DC
Name	SJ3-G6,5MB60-DPÖ-V1
Order number	08313036521
Switching distance	3 mm
Mounting	 shielded
Switch type	 N.C.
Signal Type	DC PNP
Connection	connector M8
Connection diagramm	
Dimension (in mm)	D 6,5 x 60
Technical Specification	
Operating voltage	10 - 30 VDC
Max. ripple	≤ 10 %
Voltage drop	1 V
Max. load current	200 mA
No load current	≤ 10 mA
Leakage current	≤ 10 µA
Switching frequency	1000
Switching hysteresis	≤ 15 %
Operating temperature	-25 ° C to 70 ° C
Temperature drift	≤ 10 %
Repeat accuracy	< 2 %
Switching state	LED
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2: 2008
Housing material	Brass, nickel plated
Material active face	POM
Utilisation category	DC 13
Termination	Connector M8 3pin



SJ3-G6,5MB60-DPÖ-V1

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Errors and omissions exceptet