


[Article Page](#)

Product Description		inductive sensor AC/DC	
Name	KJ2-M12MB70-VZÖ		
Order number	08317251300		
Switching distance	2 mm		
Mounting	 shielded		
Switch type	 N.C.		
Signal Type	AC/DC		
Connection	 Cable		
Connection diagramm			
Dimension (in mm)	fine-pitch thread M12 x 70		
Technical Specification			
Operating voltage	20 - 250 V AC/DC		
Voltage drop	5 V		
Max. load current	300 mA		
Leakage current	≤ 1,7 mA		
Switching frequency	30		
Switching hysteresis	≤ 15 %		
Operating temperature	-25 ° C to 70 ° C		
Temperature drift	≤ 10 %		
Repeat accuracy	≤ 5 %		
Switching state	LED		
Digital output			
Short-circuit proof	yes		
Overload protection	yes		
Reverse voltage protection	yes		
Protection category	IP67		
EMC-level	DIN EN 60947-5-2:2008		
Material active face	PCB		
Termination	2m PVC 3x0,5mm²		

werden.

Notes

Kurzschluss- und Überlastungsschutz rastend. Nach Beseitigung des Kurzschlusses muß die Spannungsversorgung für ca. 2s unterbrochen

Errors and omissions excepted