


[Article Page](#)

Product Description		capacitive sensor DC
Name	SC30-M30MN90-DPS-V2	
Order number	08323303012	
Switching distance	30 mm	
Mounting	 non shielded	
Switch type	 N.O.	
Signal Type	DC PNP	
Connection	 Connector	

Connection diagramm



Dimension (in mm)	fine-pitch thread M30 x 90
-------------------	----------------------------

Technical Specification	
Operating voltage	10 - 30 VDC
Max. ripple	$\leq 10 \%$
Voltage drop	2 V
Max. load current	200 mA
No load current	$\leq 10 \text{ mA}$
Leakage current	$\leq 10 \mu\text{A}$
Switching frequency	100
Switching hysteresis	$\leq 15 \%$
Operating temperature	-25 ° C to 70 ° C
Temperature drift	$\leq 10 \%$
Repeat accuracy	$\leq 5 \%$
Switching state	LED
Digital output	
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2:2008
Material active face	PBT
Termination	Connector M12 4pol



SC30-M30MN90-DPS-V2

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Errors and omissions excepted