


[Article Page](#)

Product Description		capacitive sensor DC	
Name	SC3-M8MN45-DPS		
Order number	08323080310		
Switching distance	3 mm		
Mounting	 non shielded		
Switch type	 N.O.		
Signal Type	DC PNP		
Connection	 Cable		
Connection diagramm			
Dimension (in mm)	fine-pitch thread M8 x 45		
Technical Specification			
Operating voltage	10 - 30 VDC		
Max. ripple	≤ 10 %		
Voltage drop	2 V		
Max. load current	200 mA		
No load current	≤ 10 mA		
Leakage current	≤ 10 µA		
Switching frequency	100		
Switching hysteresis	≤ 15 %		
Operating temperature	-25 ° C to 70 ° C		
Temperature drift	≤ 10 %		
Repeat accuracy	≤ 5 %		
Switching state	LED		
Digital output			
Short-circuit proof	yes		
Overload protection	yes		
Reverse voltage protection	yes		
Protection category	IP67		
EMC-level	DIN EN 60947-5-2:2008		
Material active face	POM		
Termination	2m PUR 3x0,15 mm²		



SC3-M8MN45-DPS

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Errors and omissions excepted