


[Article Page](#)


Product Description

inductive sensor DC



Name	KJ10-M12MN50-DPS
Order number	08317825200
Matchcode	9982-5200
Switching distance	10 mm
Mounting	 non shielded
Switch type	 N.O.
Signal Type	DC PNP
Connection	 Cable

Connection diagramm



Dimension (in mm)	fine-pitch thread M12 x 50
-------------------	----------------------------

Technical Specification

Operating voltage	10 - 30 VDC
Max. ripple	$\leq 10 \%$
Voltage drop	1 V
Max. load current	200 mA
No load current	$\leq 10 \text{ mA}$
Leakage current	$\leq 10 \mu\text{A}$
Switching frequency	500 Hz
Switching hysteresis	$\leq 15 \%$

Operating temperature	-25 ° C to 70 ° C
Temperature drift	< 10 %
Repeat accuracy	≤ 5 %
Switching state	LED
Time delay	300 ms
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2:2008
Housing material	Brass, nickel plated
Material active face	PBT
Cable length	2 m
Utilisation category	DC 13
Cable material	PVC LIYY grau (grey)
Nominal operating voltage	24 V DC
Cable cross	3x0.34 mm ²

Errors and omissions exceptet