



[Article Page](#)

Product Description

inductive sensor DC



Name	SJ12-M18MB65-DNÖ
Order number	08313181247
Switching distance	12 mm
Mounting	 shielded
Switch type	 N.C.
Signal Type	DC NPN
Connection	 Cable
Connection diagramm	

Dimension (in mm)	fine-pitch thread M18 x 65
-------------------	----------------------------

Technical Specification

Special features	quasi-shielded mounting
Operating voltage	10 - 30 VDC
Max. ripple	$\leq 10 \%$
Voltage drop	2 V
Max. load current	200 mA
No load current	$\leq 10 \text{ mA}$
Leakage current	$\leq 50 \mu\text{A}$
Switching frequency	500 Hz
Switching hysteresis	$\leq 15 \%$

Operating temperature	-25 ° C to 70 ° C
Temperature drift	≤ 10 %
Repeat accuracy	≤ 5 %
Switching state	LED
Time delay	300 ms
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2:2008
Housing material	Brass, nickel plated
Material active face	PBT
Cable length	2 m
Utilisation category	DC 13
Cable material	PVC LIYY grau (grey)
Nominal operating voltage	24 V DC
Cable cross	3x0.34 mm ²

Errors and omissions exceptet