




[Article Page](#)

Product Description	inductive tube sensor
	

Name	KJ16-Q16KN-DPS-X0337
Order number	08310001891
Switching distance	16 mm
Mounting	 non shielded
Switch type	 N.O.
Signal Type	DC PNP
Connection	connector M12
Connection diagramm	

Dimension (in mm)	S 19 x 11 x 78
-------------------	----------------

Technical Specification	
Special features	Tube sensor with output combination
	static/dynamic
	Impulse delay 100ms
Operating voltage	10 - 30 V DC
Max. ripple	≤ 10 %
Voltage drop	2,4 V
Max. load current	200 mA
No load current	≤ 10 mA

Leakage current	$\leq 10 \mu\text{A}$
Switching hysteresis	$\leq 15 \%$
Operating temperature	-25 ° C to 70 ° C
Temperature drift	$\leq 10 \%$
Repeat accuracy	$\leq 10 \%$
Switching state	LED
Digital output	static - dynamic output function
Time delay	300 ms
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP67
EMC-level	DIN EN 60947-5-2: 2008
Housing material	Plastic
Cable length	100 mm
Utilisation category	DC 13
Cable material	PUR
Cable cross	3x0.34 mm ²
Termination	Pigtail M12 3pin 100mm

Errors and omissions excepted