



[Article Page](#)

Product Description

color sensor



Name SPECTRO-3-30-POL

Order number 08386269043

Switch type  digital


Signal Type PNP/NPN

Illuminant  White light

Connection  Socket


Polschema

SPS
Binder 712, 8 pol.



1 wh GND (0V)
2 bn +24V DC ($\pm 10\%$)
3 gn IN 0
4 ye OUT 0
5 gy OUT 1
6 pk OUT 2
7 bu OUT 3
8 rd OUT 4

PC
Binder 707, 4 pol.



1 +24V DC
2 GND (0V)
3 RxD
4 TxD

Dimension (in mm) M34 x 131

Technical Specification

Special features	Polarisation filter (for very strong reduction of gloss effect), Color and gray scale detection
Operating voltage	22,60 - 26,40 V DC
Max. load current	100 mA
No load current	≤ 180 mA
Switching frequency	35 kHz
Temperature drift	< 0,01 % / °C
Repeat accuracy	+/- 1 Digit
Swiching state	LED
Digital output	, OUT 0 ... OUT 4, digital (0V/+Ub), 100 mA max. switching current npn, pnp-output available (bright-, dark-switching can be switched over)
Natural extraneous light	5000 Lux
Artificial extraneous light	5000 Lux
Material of light outlet	Glas
Impulse delay	einstellbar/ adjustable 0 ms ... 100 ms
Amplifying adjustable	8 fach/ 8-fold
Tolerance limit adjustable	ja
Working range	from 10 to 40 mm
Short-circuit proof	yes
Overload protection	yes
Reverse voltage protection	yes
Protection category	IP64 (Optik IP67)
EMC-level	DIN EN 60947-5-2
Housing material	Aluminum
Termination	connection to PLC: 8-pole fem. connector (Binder Series 712), connection to PC: 4-pole fem. connector (Binder Series 707)

Errors and omissions exceptet