



Capacitive Sensors S26 Series 80 - PNP - StEx - ATEX

Type of construction Ø 22 mm

- For use in areas with the risk of dust explosion, zone 20
- Housing material: PTFE
- With flange connector M 12 x 1

DMT 01 ATEX E 157

IECEx BVS 07.0015

Ex II 1/2 D Ex ta/tb IIIC T101°C Da/Db



Ex ta/tb IIIC T101°C Da/Db



Technical data	Non-flush mountable
Level sensor, in contact with the product	Medium dependent adjustable
Operating distance min. / max. adjustable	0...20 mm
Electrical version	4-pin DC
Output function	Antivalent
Type PNP current	KAS-80-26/113-A-D22-PTFE-Y5-1-HP-1/2D
Type PNP	KAS-80-26-A-K-22-PTFE-Y5-StEx
Art.-No.	KA 1413
Operating voltage (U _B)	10...30 V DC
Voltage drop max. (U _D)	≤ 2.0 V
Permitted residual ripple max.	10 %
Operating current (I _e)	2 x 0...150 mA
No-load current (I _o)	Typ. 15 mA
Frequency of operating cycles max.	50 Hz
Permitted ambient temperature	-20...+90 °C / CIP 121 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection	Flange connector M 12 x 1
Housing material	PTFE (FDA 21 CFR 177.1550)
Active surface	PTFE (FDA 21 CFR 177.1550)
Lid	PC (FDA 21 CFR 177.1580)
Media optimized	Yes
Matching connectors (not delivered with the sensor)	#193391, #193392

Capacitive Sensors S26 with hemispherical active surface for level control of products with a dielectric constant ϵ_r from 1,1. Products can be:

- Bulk material, like plastic granules, powder, cereals, etc.
- Liquids, like water, juice, wine, oil, chemicals or pharmaceutical solutions and much more.
- Pastes in the food, pharmaceutical and cosmetics industry



* With sealed potentiometer screw

Made in Germany