



LeVeL Capacitive Filling Level Probe - KFI

Analogue current output 4...20 mA



2 programmable limit value switching points

- Integrated evaluation electronics
- Housing material: GFK, Ø 16 mm
- Connection head and process connection stainless steel VA no. 1.4305 / AISI 303
- Process connection G1"
- Multifunction probe: Automatic identification of NPN / PNP function
- Normally open / normally closed function switchable
- Electronic lock



Technical data

Active zone [mm]	150 mm
Electrical version	5 - pin DC
Output function	Analogue, 2 limit value switching points, Normally open / normally closed switchable
Type	KFI-12-235-150-GFK/VA b-D16-G1-IL4-ETF-Y10
Art.-No.	KI 0008
Operating voltage (U _B)	18...30 V DC
Permitted residual max.	5 %
Load resistance (R _L)	≤ 400 Ohm
Output current	100 mA
Power consumption (outputs no-load)	0,8 W
Analogue output	4...20 mA
Switching frequency max.	1 Hz
Permitted ambient temperature	-25...+55 °C
Permitted ambient temperature (for active zone)	-25...+100 °C
Pressure	10 bar
LED-Display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67
Norm	EN 60947-5-2*
Connection	Flange connector M 12 x 1
Housing material	VA No. 1.4305 / AISI 303 / polyester
Active zone	GFK
For matching connectors please see our selection of accessories.	



Other housing materials for the active zone (probe), like PE, PTFE, PVDF or PEEK on request.

All specifications are subject to change without notice. (27.05.2019)

*Where applicable

Made in Germany