





Capacitive Sensors Series 95 - AC / DC - Relay Output

Housing Ø 32 mm

- Housing material: PBT
- Sensing distance 2...25 mm adjustable
- Potential-free change-over contact



Technical data	Non-flush mountable
Level sensor, in contact with the product	Medium dependent adjustable
Operating distance min. / max. adjustable	2...25 mm
Electrical version	5-wire AC / DC
Output function	Relay, 1 CO
Type	KAS-95-35-1CO-D30-PBT-Z05-1-HP
Art.-No.	KA 1065
Operating voltage (U _B)	20...250 AC / DC
Load max. AC (I, U, P)	2 A, 250 V, 60 VA
Load max. DC (I, U, P)	2 A, 220 V, 60 W
No-load current (I ₀)	2,1 mA
Frequency of operating cycles max.	2 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection cable	5 m, PVC, 5 x 0,34 mm ²
Housing material	PBT
Active surface	PBT
Lid	PA
Accessories (not supplied with the sensor): Control tube (#190710) and sensor holder (#190711) please see our selection of accessories.	



*With sealed potentiometer

Made in Germany