





Capacitive Sensor Series 80 - PNP

Housing M 32 x 1.5

- Capacitive sensor for level and position control
- Housing material: Stainless steel VA No. 1.4305 (AISI 303)
- Sensing distance 1...40 mm adjustable



Technical data	Non-flush mountable
Operating distance S_n	25 mm
Operating distance min. / max. adjustable	1...40 mm
Electrical version	4-wire DC
Output function	Antivalent
Type PNP	KAS-80-35-A-M32-PTFE/VAb-Z02-1-HP
Art.-No.	818 540
Operating voltage (U_B)	10...35 V DC
Voltage drop max. (U_d)	$\leq 2,0$ V
Permitted residual ripple max.	10 %
Operating current (I_e)	2 x 0...250 mA
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	50 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection cable	2 m, PVC, 4 x 0.50 mm ²
Housing material	Stainless steel VA No. 1.4305 (AISI 303)
Active surface	PTFE (FDA 21 CFR 177.1550)
Lid	PA / PPO
Media optimized	Yes
Accessories (delivered with the sensor)	2 nuts M 32 x 1.5



* With sealed potentiometer screw

Made in Germany